



THE FINAL BARRIER AGAINST ABRASION, CHEMICALS AND HEAT

HYTEX® 500 NOMEX® INDUSTRIAL TEXTILES

HYTEX® 500 NOMEX® INDUSTRIAL TEXTILES are manufactured from various Nomex® yarns to produce products with excellent resistance to chemicals and abrasion. In addition, Nomex® has excellent thermal insulation protection against short-term flame impingement.



AVERAGE PHYSICAL PROPERTIES

Composition	Aromatic Polyamide
Color	White
Use Limit, continuous	400°F • 204°C
Melting Point	Decomposes @ 800°F • 425°C

HYTEX® 500 PRODUCTS

PRODUCT	TYPE	WIDTH/DIAMETER	THICKNESS
Cloth	Woven	38" to 60"	Various
Tape	Woven	1/4" to 5"	Various
	Knit	1/4" to 6"	.062" to .125"
Sleeving	Braided	1/4" to 4"	.062" to .125"
	Knit	1/4" to 4"	.062" to .125"
Rope	Braided	1/8" to 2"	
	Knit	1/8" to 1-1/2"	

Tolerance is +/- 10% unless otherwise stated.

The technical data presented herein are indicative of representative properties and are intended as a specification guide only. No warranties are expressed or implied as application conditions are beyond our control. Nomex® is a registered trademark of the E.I. DuPont Company, Wilmington, DE.