




THE FINAL BARRIER AGAINST ABRASION, CHEMICALS AND HEAT

ARMATEX® SILVERSTAR 13 SILICONE COATED FIBERGLASS



ARMATEX® SILVERSTAR 13 SILICONE COATED FIBERGLASS is comprised of a strong, flexible woven fiberglass fabric impregnated both sides with premium silicone rubber to a finished weight of 13 ounces per square yard. With increased thermal properties, ARMATEX® SILVERSTAR 13 SILICONE COATED FIBERGLASS is manufactured to exceed industry standards for the fabrication of thermal insulation blankets and composite components associated with industrial insulation systems.

AVERAGE PHYSICAL PROPERTIES

Coating	Proprietary Premium Silicone Rubber
Color	Silver
Weave	Twill
Fiber Type	E-Glass
Count	7 x 8
Thickness, inches • mm, nominal	0.012 • 0.30
Temperature Rating	
Base Fabric	1000°F • 538°C
Coating	450°F • 232°C, transient exposure to 600°F • 315°C
Weight, oz/sy, nominal	13
Width, inches	38 (+/- 3%)
Standard Roll Size	50 LY

Tolerance is +/- 10% unless otherwise stated.

The technical data presented herein are indicative of representative properties and are intended as a specification guide only. No warranties are expressed or implied as application conditions are beyond our control.